

# EPIREZ HOT WEATHER CLASS C GROUT [380C]

Chemwatch Material Safety Data Sheet (REVIEW)

For Workplace - Small Volume Use Only.

Issue Date: 16-Jun-2006

CC317SLP

CHEMWATCH 4659-45

CD 2006/3 Page 1 of 6

## Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

### PRODUCT NAME

EPIREZ HOT WEATHER CLASS C GROUT [380C]

### SYNONYMS

### PRODUCT USE

Precision non shrink cement grout.

### SUPPLIER

Company: ITW Polymers & Fluids

Address:

100 Hassall Street

Wetherill Park

NSW, 2164

AUS

Telephone: +61 2 9757 8800

Emergency Tel: +61 2 9757 8800

Fax: 1800 803 596


### HAZARD RATINGS



## Section 2 - HAZARDS IDENTIFICATION

### STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.



### POISONS SCHEDULE

None

### RISK

Irritating to eyes and skin.

Inhalation may produce health damage\*.

Possible respiratory sensitiser\*.

Possible skin sensitiser\*.

\* (limited evidence).

### SAFETY

Do not breathe dust.

Wear eye/ face protection.

Use only in well ventilated areas.

Keep container in a well ventilated place.

To clean the floor and all objects contaminated by this material, use water and detergent.

Take off immediately all contaminated clothing.

In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.

If swallowed, IMMEDIATELY contact Doctor or Poisons Information Centre

continued...

# EPIREZ HOT WEATHER CLASS C GROUT [380C]

Chemwatch Material Safety Data Sheet (REVIEW)

For Workplace - Small Volume Use Only.

Issue Date: 16-Jun-2006

CC317SLP

CHEMWATCH 4659-45

CD 2006/3 Page 2 of 6

Section 2 - HAZARDS IDENTIFICATION

(show this container or label).

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
portland cement	65997-15-1	30-60
fly ash - low quartz	68131-74-8	<10
calcium alumina sulfate		<10
additives nonhazardous		30-60

## Section 4 - FIRST AID MEASURES

### SWALLOWED

For advice, contact a Poisons Information Centre or a doctor.

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

### EYE

If this product comes in contact with the eyes:

- Immediately hold eyelids apart and flush the eye continuously with running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

### SKIN

If skin or hair contact occurs:

- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

### INHALED

- If dust is inhaled, remove from contaminated area.
- Encourage patient to blow nose to ensure clear passage of breathing.

### NOTES TO PHYSICIAN

Treat symptomatically.

## Section 5 - FIRE FIGHTING MEASURES

### EXTINGUISHING MEDIA

- There is no restriction on the type of extinguisher which may be used.

### FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves for fire only.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

### FIRE/EXPLOSION HAZARD

- Non combustible.
- Not considered a significant fire risk, however containers may burn.

### FIRE INCOMPATIBILITY

None known.

### HAZCHEM: None

### Personal Protective Equipment

- Breathing apparatus.
- Gas tight chemical resistant suit.
- Limit exposure duration to 1 BA set 30 mins.

continued...

# EPIREZ HOT WEATHER CLASS C GROUT [380C]

Chemwatch Material Safety Data Sheet (REVIEW)

For Workplace - Small Volume Use Only.

Issue Date: 16-Jun-2006

CC317SLP

CHEMWATCH 4659-45

CD 2006/3 Page 3 of 6

## Section 6 - ACCIDENTAL RELEASE MEASURES

### EMERGENCY PROCEDURES

#### MINOR SPILLS

- Clean up all spills immediately.
- Avoid contact with skin and eyes.
- Wear protective clothing, gloves, safety glasses and dust respirator.
- Use dry clean up procedures and avoid generating dust.
- Sweep up or
- Vacuum up (consider explosion-proof machines designed to be grounded during storage and use).
- Place in clean drum then flush area with water.

#### MAJOR SPILLS

- Clear area of personnel and move upwind.
- If inhalation risk of exposure exists, wear SAA approved dust respirator.
- Collect recoverable product into labelled containers for recycling.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

## Section 7 - HANDLING AND STORAGE

### PROCEDURE FOR HANDLING

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

### SUITABLE CONTAINER

Multi ply paper bag with sealed plastic liner or heavy gauge plastic bag

NOTE: Bags should be stacked, blocked, interlocked, and limited in height so that they are stable and secure against sliding or collapse. Check that all containers are clearly labelled and free from leaks. Packing as recommended by manufacturer.

### STORAGE INCOMPATIBILITY

Segregate from strong acids.

### STORAGE REQUIREMENTS

Keep dry.

Absorbs water and carbon dioxide from the air.

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m <sup>3</sup>	STEL ppm	STEL mg/m <sup>3</sup>	Peak ppm	Peak mg/m <sup>3</sup>	TWA F/CC
Australia Exposure Standards	portland cement (Portland cement (a))		10					

continued...

# EPIREZ HOT WEATHER CLASS C GROUT [380C]

Chemwatch Material Safety Data Sheet (REVIEW)

For Workplace - Small Volume Use Only.

Issue Date: 16-Jun-2006

CC317SLP

CHEMWATCH 4659-45

CD 2006/3 Page 4 of 6




## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Source	Material	TWA ppm	TWA mg/m <sup>3</sup>	STEL ppm	STEL mg/m <sup>3</sup>	Peak ppm	Peak mg/m <sup>3</sup>	TWA F/CC
--------	----------	------------	--------------------------	-------------	---------------------------	-------------	---------------------------	-------------

The following materials had no OELs on our record under the following CAS or Chemwatch (CW) numbers

- Epirez Hot Weather Class C Grout [380C]: No data available for CW:4659-45
- portland cement: No data available for
- 330: No data available for
- fly ash - low quartz: No data available for CAS:68131-74-8 CW:564194

### PERSONAL PROTECTION



#### RESPIRATOR

Particulate

#### EYE

- Safety glasses with side shields; or as required,
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

#### HANDS/FEET

Wear chemical protective gloves, eg. PVC.  
Wear safety footwear or safety gumboots, eg. Rubber.

#### OTHER

- Overalls.
- Eyewash unit.

### ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas.

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

### APPEARANCE

Grey powder with no odour; insoluble in water. Hardens after reaction with water.

### PHYSICAL PROPERTIES

Solid.

Molecular Weight: Not applicable.

Melting Range (°C): Not applicable

Solubility in water (g/L): Reacts

pH (1% solution): Not available.

Volatile Component (%vol): Not applicable

Relative Vapour Density (air=1): Not applicable.

Lower Explosive Limit (%): Not applicable

Autoignition Temp (°C): Not applicable

State: Divided solid

Boiling Range (°C): Not applicable

Specific Gravity (water =1): >1

pH (as supplied): Not applicable

Vapour Pressure (kPa): Not applicable.

Evaporation Rate: Not applicable

Flash Point (°C): Not Applicable

Upper Explosive Limit (%): Not applicable

Decomposition Temp (°C): Not applicable

Viscosity: Not Applicable

continued...

# EPIREZ HOT WEATHER CLASS C GROUT [380C]

Chemwatch Material Safety Data Sheet (REVIEW)  
For Workplace - Small Volume Use Only.  
Issue Date: 16-Jun-2006  
CC317SLP

CHEMWATCH 4659-45  
CD 2006/3 Page 5 of 6

---

## Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

---

### CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

---

## Section 11 - TOXICOLOGICAL INFORMATION

---

### POTENTIAL HEALTH EFFECTS

#### ACUTE HEALTH EFFECTS

Irritating to eyes and skin.  
Inhalation may produce health damage\*.  
\* (limited evidence).

#### CHRONIC HEALTH EFFECTS

Possible respiratory sensitiser\*.  
Possible skin sensitiser\*.  
\* (limited evidence).

### TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

---

## Section 12 - ECOLOGICAL INFORMATION

---

No data

---

## Section 13 - DISPOSAL CONSIDERATIONS

---

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- Bury residue in an authorised landfill.
- Recycle containers if possible, or dispose of in an authorised landfill.

---

## Section 14 - TRANSPORTATION INFORMATION

---

HAZCHEM: None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS:UN

---

## Section 15 - REGULATORY INFORMATION

---

POISONS SCHEDULE: None

### REGULATIONS

portland cement (CAS: 65997-15-1) is found on the following regulatory lists;

Australia Exposure Standards  
Australia High Volume Industrial Chemical List (HVICL)  
Australia Inventory of Chemical Substances (AICS)  
OECD Representative List of High Production Volume (HPV) Chemicals

fly ash - low quartz (CAS: 68131-74-8) is found on the following regulatory lists;

Australia Inventory of Chemical Substances (AICS)  
International Council of Chemical Associations (ICCA) - High Production Volume List  
OECD Representative List of High Production Volume (HPV) Chemicals

continued...

# EPIREZ HOT WEATHER CLASS C GROUT [380C]

Chemwatch Material Safety Data Sheet (REVIEW)

For Workplace - Small Volume Use Only.

Issue Date: 16-Jun-2006

CC317SLP

CHEMWATCH 4659-45

CD 2006/3 Page 6 of 6

---

## Section 16 - OTHER INFORMATION

---

*This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.*

**Issue Date: 16-Jun-2006**

**Print Date: 12-Sep-2006**